

NewLook® International, Inc. TiqueWash™

Color Chart & Technical Information Sheet



NewLook International, Inc. **TiqueWash** is a superior antiquing colorant used to easily create a natural, multi-toned finish on textured concrete surfaces. The high-quality water based formula includes ultra-fine polymers for improved surface penetration and strong adhesion when sealed with NewLook SmartSeal™ or other compatible sealers. The TiqueWash powder is mixed with water to create a translucent color wash that, once applied, runs off high spots and settles in the low areas of relief of textured concrete. Use TiqueWash to restore the color of weathered concrete or create an antique color finish for stamped surfaces.

USES & BENEFITS

- Restore the color of weathered (textured) concrete
- Create an antique, two-toned color finish on stamped concrete surfaces
- Strong bond when sealed with NewLook SmartSeal AU, SmartSeal WB, or other compatible sealers
- Low hazing properties
- Fade resistant pigmentation resists UV damage

INSTRUCTIONS

Preparation

Thoroughly clean the concrete surface before applying TiqueWash. Remove existing sealer and other foreign materials using NewLook EasyStrip™ and Mean Klean™ Concrete Degreaser. New concrete may need to be slightly etched using NewLook EcoAcid™ to achieve desired porosity. The concrete must be clean and free of any foreign materials or bond-breakers that might inhibit the stain's ability to bond with the surface.

Installation

Using the included measuring cup, mix into a separate 5-gallon bucket one to three scoops of TiqueWash powder (depending on desired color intensity) with one gallon of clean water. On average, one scoop is sufficient. Pre-moisten the surface with water to help ensure color consistency and proper settling of the pigments. Spread mixed TiqueWash across the surface with a NewLook Applicator Brush™ or clean, soft push broom. Apply a liberal and uniform amount of material. Keep the product mixture agitated throughout the installation process to ensure color consistency and prevent pigment from settling in the container.

Allow TiqueWash to thoroughly dry on the surface. The color will lighten as it dries. Once dry, apply NewLook SmartSeal WB, SmartSeal AU or other compatible sealers according to instructions. Clean up with water.

COVERAGE

One three (3) pound container covers approximately 2000–3000 square feet. A mixed gallon of material covers an average of 200 square feet.

STORAGE

Store unmixed TiqueWash in a cool, dry place (in temperatures below 120° F). Shelf life is approximately two (2) years when containers are kept tightly sealed.

COLOR GUIDE (APPROXIMATE)

 Dark Gray TW-101	 Medium Gray TW-102	 Light Gray TW-103	 Arctic Chill TW-104
 Sahara Night TW-105	 Aged Coral TW-106	 Terra Cotta TW-107	 Sea Foam TW-108
 Smokey Quartz TW-109	 Antique Umber TW-110	 Saddle Dust TW-111	 Seasoned Earth TW-112
 Sycamore TW-113	 Jasper TW-114	 Island Spray TW-115	 Evening Oak TW-116

NOTE: The colors shown are for reference only and should not be used for final color selection. For best results, select your color from a (printed) Color Selection Chart and within the same light source in which product will be applied. In other words, your screen resolution will affect the color appearance. The colors shown are approximate and, as close as possible, represent sealed areas of relief or texture on stamped concrete where TiqueWash will puddle and dry to achieve its darkest, most concentrated color.

LIMITED PRODUCT WARRANTY

This product is warranted to be of uniform quality within manufacturer's tolerances. NewLook International, Inc. has no control over the use of TiqueWash ("Product"), therefore no other oral or written representation or statement of any kind, express or implied, now or hereafter made is authorized or warranted by NewLook or its affiliates, and NewLook and its affiliates hereby disclaims all such warranties. The end user shall be responsible for determining Product suitability, including surface conditions and climate conditions, and end user assumes all risks and liability. NewLook shall not be liable for special, incidental, or consequential damages, including delays or lost profits. Communication of this warranty and its limitations to end users is not the responsibility of NewLook but should be communicated by those in direct contact with the end user. Any claim regarding product defect must be received in writing within one year from the date of manufacture. No claim will be considered without such written notice or after the specified time interval. Product is intended to be used by licensed contractors and installers, experienced and trained in the use of Product. Please use common sense.

CAUTION: KEEP AWAY FROM CHILDREN. Do not ingest. Please use common sense.